

**HYDROFUGE INCOLORE - 3L00314**

**SAFETY DATA SHEET**

(REACH regulation (EC) n° 1907/2006 - n° 2015/830)

**SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1. Product identifier**

Product name : HYDROFUGE INCOLORE  
Product code : 3L00314.

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Consumer and professional application of coatings

**1.3. Details of the supplier of the safety data sheet**

Registered company name : Tollens Division Professionnelle.  
Address : 71 Boulevard du Général Leclerc.92583.CLICHY Cedex.FRANCE.  
Telephone : 01 41 27 62 00. Fax : 01 41 27 62 01.  
support.fds@cromology.com

**1.4. Emergency telephone number : +33 (0)1 45 42 59 59.**

Association/Organisation : INRS / ORFILA <http://www.centres-antipoison.net>.

**Other emergency numbers**

National Poisons Information Service (NPIS) : Email: [director.birmingham.unit@npis.org](mailto:director.birmingham.unit@npis.org) and Website: <http://www.npis.org/>

**SECTION 2 : HAZARDS IDENTIFICATION**

**2.1. Classification of the substance or mixture**

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Flammable liquid, Category 3 (Flam. Liq. 3, H226).  
Repeated exposure may cause skin dryness or cracking (EUH066).  
Specific target organ toxicity (single exposure), Category 3 (STOT SE 3, H336).  
Aspiration hazard, Category 1 (Asp. Tox. 1, H304).  
This mixture does not present an environmental hazard. No known or foreseeable environmental damage under standard conditions of use.

**2.2. Label elements**

Mixture for spray application.

**In compliance with EC regulation No. 1272/2008 and its amendments.**

Hazard pictograms :



GHS02



GHS07



GHS08

Signal Word :

DANGER

Product identifiers :

EC 919-857-5 HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS

Hazard statements :

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H336 May cause drowsiness or dizziness.  
EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.  
P102 Keep out of reach of children.

Precautionary statements - Prevention :

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### HYDROFUGE INCOLORE - 3L00314

P260	Do not breathe vapours and spray.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary statements - Response :	
P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER or a doctor.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
Precautionary statements - Storage :	
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
Precautionary statements - Disposal :	
P501	Dispose of this material and its container to hazardous or special waste collection point.

#### 2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC)  $\geq 0.1\%$  published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

### SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

##### Composition :

Identification	(EC) 1272/2008	Note	%
EC: 919-857-5 REACH: 01-2119463258-33-  HYDROCARBONS, C9-C11, N-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS	GHS08, GHS07, GHS02 Dgr Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336 EUH:066	P	50 $\leq$ x % < 100
CAS: 64742-48-9 EC: 265-150-3  NAPHTHA (PETROLEUM), HYDROTREATED HEAVY	GHS08 Dgr Asp. Tox. 1, H304 EUH:066	P	2.5 $\leq$ x % < 10

(Full text of H-phrases: see section 16)

##### Information on ingredients :

Note P: The carcinogen or mutagen classification does not apply because the substance contains less than 0.1 % w/w of benzene (EINECS 200-753-7).

### SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.

#### 4.1. Description of first aid measures

##### In the event of exposure by inhalation :

In the event of massive inhalation, remove the person exposed to fresh air. Keep warm and at rest.

If the person is unconscious, place in recovery position. Notify a doctor in all events, to ascertain whether observation and supportive hospital care will be necessary.

If breathing is irregular or has stopped, effect mouth-to-mouth resuscitation and call a doctor.

In the event of inhalation of spray mist, seek medical attention immediately, showing the packaging or label.

##### In the event of splashes or contact with eyes :

Wash thoroughly with fresh, clean water for 15 minutes holding the eyelids open.

##### In the event of splashes or contact with skin :

Remove contaminated clothing and wash the skin thoroughly with soap and water or a recognised cleaner.

Watch out for any remaining product between skin and clothing, watches, shoes, etc.

**HYDROFUGE INCOLORE - 3L00314**

If the contaminated area is widespread and/or there is damage to the skin, a doctor must be consulted or the patient transferred to hospital.

**In the event of swallowing :**

Do not give the patient anything orally.

In the event of swallowing, if the quantity is small (no more than one mouthful), rinse the mouth with water and consult a doctor.

Seek medical attention, showing the label.

If swallowed accidentally, call a doctor to ascertain whether observation and hospital care will be necessary. Show the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

No data available.

**4.3. Indication of any immediate medical attention and special treatment needed**

No data available.

**SECTION 5 : FIREFIGHTING MEASURES**

Flammable.

Chemical powders, carbon dioxide and other extinguishing gas are suitable for small fires.

**5.1. Extinguishing media**

Keep packages near the fire cool, to prevent pressurised containers from bursting.

**Suitable methods of extinction**

In the event of a fire, use :

- sprayed water or water mist
- water with AFFF (Aqueous Film Forming Foam) additive
- halon
- foam
- multipurpose ABC powder
- BC powder
- carbon dioxide (CO<sub>2</sub>)

Prevent the effluent of fire-fighting measures from entering drains or waterways.

**Unsuitable methods of extinction**

In the event of a fire, do not use :

- water jet

**5.2. Special hazards arising from the substance or mixture**

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**5.3. Advice for firefighters**

Fire-fighting personnel are to be equipped with autonomous insulating breathing apparatus.

**SECTION 6 : ACCIDENTAL RELEASE MEASURES**

**6.1. Personal precautions, protective equipment and emergency procedures**

Consult the safety measures listed under headings 7 and 8.

**For non first aid worker**

Because of the organic solvents contained in the mixture, eliminate sources of ignition and ventilate the area.

Avoid inhaling the vapors.

Avoid any contact with the skin and eyes.

If a large quantity has been spilt, evacuate all personnel and only allow intervention by trained operators equipped with safety apparatus.

**HYDROFUGE INCOLORE - 3L00314**

**For first aid worker**

First aid workers will be equipped with suitable personal protective equipment (See section 8).

**6.2. Environmental precautions**

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

**6.3. Methods and material for containment and cleaning up**

Clean preferably with a detergent, do not use solvents.

**6.4. Reference to other sections**

No data available.

**SECTION 7 : HANDLING AND STORAGE**

Requirements relating to storage premises apply to all facilities where the mixture is handled.

**7.1. Precautions for safe handling**

Always wash hands after handling.

Remove and wash contaminated clothing before re-using.

Ensure that there is adequate ventilation, especially in confined areas.

**Fire prevention :**

Handle in well-ventilated areas.

Vapours are heavier than air. They can spread along the ground and form mixtures that are explosive with air.

Prevent the formation of flammable or explosive concentrations in air and avoid vapor concentrations higher than the occupational exposure limits.

Never inhale this mixture.

Prevent the accumulation of electrostatic charges with connections to earth.

The mixture can become electrostatically charged : always earth during decanting operations. Wear antistatic shoes and clothing and floors should be electrically non-conductive.

Use the mixture in premises free of naked flames or other sources of ignition and ensure that electrical equipment is suitably protected.

Keep packages tightly closed and away from sources of heat, sparks and naked flames.

Do not use tools which may produce sparks. Do not smoke.

Prevent access by unauthorised personnel.

**Recommended equipment and procedures :**

For personal protection, see section 8.

Observe precautions stated on label and also industrial safety regulations.

Where the personnel must carry out work in a booth, whether for spraying or otherwise, the ventilation may be inadequate to control particles and solvent vapors in every case.

It is therefore recommended that personnel wear masks with a compressed air supply during spraying operations until the concentration of particles and solvent vapors has fallen below the exposure limits.

Avoid inhaling vapors. Carry out any industrial operation which may give rise to this in a sealed apparatus.

Provide vapor extraction at the emission source and also general ventilation of the premises.

Also provide breathing apparatus for certain short tasks of an exceptional nature and for emergency interventions.

In all cases, recover emissions at source.

Packages which have been opened must be reclosed carefully and stored in an upright position.

**Prohibited equipment and procedures :**

No smoking, eating or drinking in areas where the mixture is used.

**7.2. Conditions for safe storage, including any incompatibilities**

No data available.

**Storage**

Keep out of reach of children.

Keep the container tightly closed in a dry, well-ventilated place.

Keep away from food and drink, including those for animals.

## HYDROFUGE INCOLORE - 3L00314

Keep away from all sources of ignition - do not smoke.

Keep well away from all sources of ignition, heat and direct sunlight.

Avoid accumulation of electrostatic charges.

The floor must be impermeable and form a collecting basin so that, in the event of an accidental spillage, the liquid cannot spread beyond this area.

### Packaging

Always keep in packaging made of an identical material to the original.

### 7.3. Specific end use(s)

No data available.

## SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control parameters

No data available.

### 8.2. Exposure controls

#### Personal protection measures, such as personal protective equipment

Pictogram(s) indicating the obligation of wearing personal protective equipment (PPE) :



Use personal protective equipment that is clean and has been properly maintained.

Store personal protective equipment in a clean place, away from the work area.

Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

#### - Eye / face protection

Avoid contact with eyes.

Use eye protectors designed to protect against liquid splashes

Before handling, wear safety goggles in accordance with standard EN166.

#### - Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN374.

Gloves must be selected according to the application and duration of use at the workstation.

Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.

Type of gloves recommended :

- Nitrile rubber (butadiene-acrylonitrile copolymer rubber (NBR))
- PVA (Polyvinyl alcohol)

Recommended properties :

- Impervious gloves in accordance with standard EN374

#### - Body protection

Avoid skin contact.

Wear suitable protective clothing.

Work clothing worn by personnel shall be laundered regularly.

After contact with the product, all parts of the body that have been soiled must be washed.

#### - Respiratory protection

Avoid breathing vapours.

If the ventilation is insufficient, wear appropriate breathing apparatus.

When workers are confronted with concentrations that are above occupational exposure limits, they must wear a suitable, approved, respiratory protection device.

Anti-gas and vapour filter(s) (Combined filters) in accordance with standard EN14387 :

- A1 (Brown)

**HYDROFUGE INCOLORE - 3L00314**

**SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES**

**9.1. Information on basic physical and chemical properties**

**General information :**

Physical state : Fluid liquid.

**Important health, safety and environmental information**

pH : Not relevant.  
Boiling point/boiling range : Not specified.  
Flash Point Interval : 23°C <= FP <= 55°C  
Vapour pressure (50°C) : Below 110 kPa (1.10 bar).  
Density : < 1  
Water solubility : Insoluble.  
Viscosity:  $\nu < 7 \text{ mm}^2/\text{s}$  (40°C)  
Melting point/melting range : Not specified.  
Self-ignition temperature : Not specified.  
Decomposition point/decomposition range : Not specified.

**9.2. Other information**

No data available.

**SECTION 10 : STABILITY AND REACTIVITY**

**10.1. Reactivity**

No data available.

**10.2. Chemical stability**

This mixture is stable under the recommended handling and storage conditions in section 7.

**10.3. Possibility of hazardous reactions**

When exposed to high temperatures, the mixture can release hazardous decomposition products, such as carbon monoxide and dioxide, fumes and nitrogen oxide.

**10.4. Conditions to avoid**

Any apparatus likely to produce a flame or to have a metallic surface at high temperature (burners, electric arcs, furnaces etc.) must not be allowed on the premises.

Avoid :

- accumulation of electrostatic charges.
- heating
- heat
- flames and hot surfaces

**10.5. Incompatible materials**

**10.6. Hazardous decomposition products**

The thermal decomposition may release/form :

- carbon monoxide (CO)
- carbon dioxide (CO<sub>2</sub>)

**SECTION 11 : TOXICOLOGICAL INFORMATION**

**11.1. Information on toxicological effects**

Exposure to vapours from solvents in the mixture in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on kidney, liver and central nervous system.

Symptoms produced will include headaches, numbness, dizziness, fatigue, muscular asthenia and, in extreme cases, loss of consciousness.

Repeated or prolonged contact with the mixture may cause removal of natural oil from the skin resulting in non-allergic contact dermatitis and absorption through the skin.

Splashes in the eyes may cause irritation and reversible damage

**HYDROFUGE INCOLORE - 3L00314**

Narcotic effects may occur, such as drowsiness, narcosis, decreased alertness, loss of reflexes, lack of coordination or dizziness.

Effects may also occur in the form of violent headaches or nausea, judgement disorder, giddiness, irritability, fatigue or memory disturbance.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

**11.1.1. Substances**

No toxicological data available for the substances.

**11.1.2. Mixture**

**Aspiration hazard :**

May be fatal if swallowed and enters airways.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

**SECTION 12 : ECOLOGICAL INFORMATION**

If the product contaminates waterways, rivers or drains, alert the relevant authorities in accordance with statutory procedures.

**12.1. Toxicity**

**12.1.2. Mixtures**

No aquatic toxicity data available for the mixture.

**12.2. Persistence and degradability**

No data available.

**12.3. Bioaccumulative potential**

No data available.

**12.4. Mobility in soil**

No data available.

**12.5. Results of PBT and vPvB assessment**

No data available.

**12.6. Other adverse effects**

No data available.

**SECTION 13 : DISPOSAL CONSIDERATIONS**

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

Conform to local regulations about water protection.

Waste and used packages must be eliminated following local regulations.

**13.1. Waste treatment methods**

Do not pour into drains or waterways.

**Waste :**

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

**Soiled packaging :**

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

**Codes of wastes (Decision 2001/573/EC, Directive 2006/12/EEC, Directive 94/31/EEC on hazardous waste) :**

08 01 11 \* waste paint and varnish containing organic solvents or other dangerous substances

15 01 04 metallic packaging

**HYDROFUGE INCOLORE - 3L00314**

**SECTION 14 : TRANSPORT INFORMATION**

Transport product in compliance with provisions of the ADR for road, RID for rail, IMDG for sea and ICAO/IATA for air transport (ADR 2015 - IMDG 2014 - ICAO/IATA 2016).

**14.1. UN number**

3295

**14.2. UN proper shipping name**

UN3295=HYDROCARBONS, LIQUID, N.O.S.

**14.3. Transport hazard class(es)**

- Classification :



3

**14.4. Packing group**

III

**14.5. Environmental hazards**

-

**14.6. Special precautions for user**

ADR/RID	Class	Code	Pack gr.	Label	Ident.	LQ	Provis.	EQ	Cat.	Tunnel
	3	F1	III	3	30	5 L	-	E1	3	D/E

IMDG	Class	2°Label	Pack gr.	LQ	EMS	Provis.	EQ
	3	-	III	5 L	F-E,S-D	223	E1

IATA	Class	2°Label	Pack gr.	Passager	Passager	Cargo	Cargo	note	EQ
	3	-	III	355	60 L	366	220 L	A3 A324	E1
	3	-	III	Y344	10 L	-	-	A3 A324	E1

For limited quantities, see part 2.7 of the OACI/IATA and chapter 3.4 of the ADR and IMDG.

For excepted quantities, see part 2.6 of the OACI/IATA and chapter 3.5 of the ADR and IMDG.

**14.7. Transport in bulk according to Annex II of Marpol and the IBC Code**

No data available.

**SECTION 15 : REGULATORY INFORMATION**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 487/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 758/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 944/2013.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 605/2014.
- EU Regulation No. 1272/2008 amended by EU Regulation No. 1297/2014.

**- Container information:**

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

**- Particular provisions :**

No data available.



**HYDROFUGE INCOLORE - 3L00314**

**15.2. Chemical safety assessment**

No data available.

**SECTION 16 : OTHER INFORMATION**

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

**Wording of the phrases mentioned in section 3 :**

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
EUH066	Repeated exposure may cause skin dryness or cracking.

**Abbreviations :**

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS02 : Flame

GHS07 : Exclamation mark

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.